



National  
Technical  
University  
of Athens



GLOBAL  
**WtERT**  
COUNCIL

aegean islands  
cyclades • dodecanese  
Region of South Aegean



# RHODES2024

## 19-22 JUNE

[rhodes2024.uest.gr](http://rhodes2024.uest.gr)

# 11<sup>th</sup> International Conference on Sustainable Solid Waste Management

[rhodes2024.uest.gr](http://rhodes2024.uest.gr) | 19-22 June, Rhodes, Greece





## Poster session

- 53 J. Milić, B. Radak, I. Petrović, J. Jakovljević, N. Vranes, B. Dunjić  
Upcycling of waste polyurethane foam into absorbent pellets
- 54 F.A.L. Sánchez, J.A.S. Pacheco, J.B. Welter, P.K. Lacava, H.M. Veit  
Thermal treatment of lithium concentrated fraction from end-of-life  $\text{LiFePO}_4$  automotive batteries as a prior process for lithium recovery
- 55 C. García-Delgado, V. Polo, B. Mayans, M.A. Jiménez-González, T. Fresno, E. Eymar, S. López-Rayó  
Agricultural valorization of seaweed from the shores of Mar Menor Lagoon by composting
- 56 R. García-Montero, M. Cortijo-Ruiz, C. García-Delgado, M. Rodríguez-Rastrero, S. López-Rayó, N. Carreras  
Effect of salinity on the production of biogas from the macroalgae *Caulerpa prolifera*
- 57 Xiao-Xiao He, Yi-Fan Zhao, Yi-Hao Chen, Yu Lu, Ying-Zhi Peng, Hong-Yu Guo, Le-YunYang, Chun-Ying Feng, Shuai You, Jun Wang  
Reduction of antibiotic contamination through replacement: Enhanced thermostability and catalytic efficiency of glucose oxidase through molecular design
- 58 L. Cutroneo, B. Benedetti, L. Caiazzo, G. Cecchi, G. Di Bella, M. Di Carro, S. Di Piazza, D. Di Trapani, L. Gaggero, I. Geneselli, E. Magi, S. Manzo, M. Montereali, L. Parrella, S. Schiavo, S. Serranti, M. Zotti, M. Capello  
The Italian National Recovery and Resilience Plan (PNRR) RETURN Project: proposal of new monitoring and bioremediation protocols in the pilot site of the Port of Genoa
- 59 Peipei Gao, Longfei Tang, Xueli Chen  
Migration characteristics of chlorine during pyrolysis of municipal solid waste pellets
- 60 L. di Bitonto, A. Li, C. Pastore  
Microalgae as sustainable and potential feedstock for the production of biofuels and fine chemicals
- 61 L. Pisicchio, B. Lleshi, E.M. Di Clemente, F. Todaro, M. Notarnicola  
Anaerobic digestion of bioplastics: potential recovery of methane from PLA and PHA shopper
- 62 L. di Bitonto, V. Locaputo, C. Pastore  
Monitoring and behaviour of organic pollutants in sewage sludge after the anaerobic digestion process
- 63 F. Di Lauro, G. Marotta, M. Balsamo, R. Solimene, M. L. Alfieri, P. Manini, P. Salatino, F. Montagnaro  
Hydrothermal liquefaction of sewage sludges mixtures: Effect of the biomolecular composition on the process performance
- 64 A. Schmuck, J.S. Coene, M. Roosen M. Roosen, L. Harinck, K. M. Van Geem, K. Ragaert, S. de Meester  
To sort or not? The impact of the collection scheme on post-consumer plastic waste feedstock quality and its suitability for mechanical and chemical recycling
- 65 S. López-Rayó, K.J. De la Fuente, B. Mayans1, T. Fresno, E. Eymar, C. García-Delgado  
Composition of seaweed from the shores of Mar Menor Lagoon with potential use in Agriculture
- 66 P. Cucuzza, E. Gorga, S. Serranti, A. Rizzo, I. Lapietra, G. Mastronuzzi, D. Mele, G. Bonifazi  
Hyperspectral imaging applied to monitoring microplastics collected from sediments of Mar Piccolo basin (Taranto, Southern Italy)
- 67 M. Dezi, D. Fino, T. Tommasi, G. Saracco, F. Demichelis  
Valorizing Organic Waste Via Arrested Anaerobic Digestion (AAD): Production of Volatile Fatty Acids (VFAs)
- 68 B. Radović, K. Baralić, M. Ćurčić, Đ. Marić, J. Živanović, E. Antonijević Miljaković, A. Buha Đorđević, D. Đukić Ćosić, Z. Bulat, B. Antonijević  
In silico prediction of potential mixture toxicity mechanisms underlying endocrine disorders as a result of e-waste recycling activities: Exposure to organophosphate flame retardants and toxic metal(oid)s

# Microalgae as sustainable and potential feedstock for the production of biofuels and fine chemicals

L. di Bitonto<sup>\*1</sup>, A. Li<sup>2</sup>, C. Pastore<sup>1</sup>

<sup>1</sup>Water Research Institute (IRSA), National Research Council (CNR), Bari, 70132, Italy

<sup>2</sup>No.19, Xijiekouwai Street, Haidian District, Beijing 100875, China

Keywords: microalgae, *Chlorella vulgaris*, wastewater treatment, biomass valorization, biorefinery.

Presenting author email: [luigi.dibitonto@ba.irsacnr.it](mailto:luigi.dibitonto@ba.irsacnr.it)

## Abstract

Microalgae have been identified as a promising and sustainable alternative for wastewater treatment. Their ability to biologically purify wastewater of different origins, using them as a growth substrate, holds great potential as a wastewater treatment method. However, the technology cost is the main factor that limits the industrial scale application. For this reason, it is necessary to introduce a downstream process of the purification process to minimize production costs. The simultaneous use of microalgae for wastewater treatment by the production of high value-added chemical compounds has made this challenge feasible and economically viable. In this work, a detailed analysis of the chemical composition of microalgae (*Chlorella Vulgaris*) recovered from wastewater treatment was carried out in order to identify the possible prospects for future reuse.

## Introduction

As a result of the growing world population and rapid industrialization, the increasing production of municipal wastewater has emerged as one of the major environmental problems. Organic and inorganic pollutants of various origins, including micropollutants and heavy metals, are discharged into water bodies nearby industrial and agricultural activities. The presence of excess nutrients such as nitrogen (N) and phosphorus (P) is the cause of eutrophication of water bodies and the resulting environmental problems. For this reason, there is a need to develop treatment processes that can remove these nutrients before wastewater is discharged. In this sense, the use of algae as a means of bioremediation of wastewater can effectively extract nitrogen and phosphorus from wastewater, keeping dissolved oxygen levels constant and helping to reduce the pathogens and fecal bacteria present in wastewater. In addition, it is also an environmentally sustainable option as it has the ability to convert carbon dioxide into chemicals and useful products, thus helping to reduce greenhouse gas emissions. However, the cost of this technology is the main factor that limits its application on an industrial scale. In order to solve this problem, the development of an integrated approach for the valorization of the produced microalgae would contribute not only to considerably reduce the total costs but to convert the produced biomass "from waste to resource" in accordance with the principles of the circular economy. In this work, a detailed analysis of the chemical composition of microalgae (*Chlorella Vulgaris*) grown using wastewater as a substrate was carried out.

The identification and quantification of esterifiable lipids, proteins, easily hydrolysable sugars (EHS), lignin and ashes were performed in order to identify the possible prospects of its possible reuse for the production of platform molecules and fine chemicals.

## Materials and Methods

### *Protocol for biomass characterization*

About 1 g of dried biomass were startingly dispersed in hexane (20 mL per three times) in order to extract lipid. Hexane phases were collected together and then evaporated until residue was weighted (lipids were even gas-chromatographically determined as methyl-esters by using a procedure of esterification in methanol and HCl Bitonto et al. (2020a)). Then, residual solids (RS) obtained from lipid extraction were desiccated at 105 °C and analysed by adapting the National Renewable Energy Laboratory (NREL) procedure to determine carbohydrate structure. Solids were weighed and transferred into a glass balloon with 100 mL of a 4% H<sub>2</sub>SO<sub>4</sub> aqueous solution. Then, this suspension was refluxed for two hours, cooled, filtered and diluted in water before analysis with HPAE-PAD for sugar determination (easily hydrolysable sugars, EHS, includes hemicellulose, pectinic sugars and exopolysaccharides) and protein content Bitonto et al. (2020b)). Then, the solids recovered from the aforementioned filtration were washed with distilled water and dried at 105 °C for 24 h. This solid was weighed and transferred into a glass tube and kept under suspension with 3 mL of 75% H<sub>2</sub>SO<sub>4</sub> at 4 °C for 24 h. After this treatment, water was added to the analyte, achieving a final volume of 100 mL; this solution was again refluxed for two hours. This resulting suspension was cooled, filtered, diluted and analysed for cellulose determination. The RS were thoroughly washed with water, dried at 105 °C for 24 h and weighed. The organic residue was calculated as the difference between this weight and the respective ash obtained after putting the same RS into an oven at 550 °C for 2 h; this difference represents the lignin content. Ashes content was determined directly on the dry sample after thermal treatment after 2 h at 550 °C. The entire protocol for biomass characterization can be summarized in Figure 1.




Figure 1. Schematic diagram for biomass characterization.

#### Identification of carboxylic acids

About 50  $\mu\text{L}$  of water solution deriving from the first digestion of dry biomass (100 mL of a 4%  $\text{H}_2\text{SO}_4$ ) were transferred in a vial with insert of a total volume of 250  $\mu\text{L}$  and dried under nitrogen flow at 40  $^\circ\text{C}$ . Then, 50  $\mu\text{L}$  of MTSFA and 50  $\mu\text{L}$  of pyridine were added. The vial was closed and left for 30 min at 40  $^\circ\text{C}$ . Finally, this solution was analysed via gas-chromatography (GC–MS).

#### Results and discussion

##### Chemical characterization of microalgae

The results of chemical characterization of microalgae (*Chlorella Vulgaris*) are reported in Tables 1. Overall, the protein content is the main component of this biomass with a value of  $556 \pm 25 \text{ mg/g}_{\text{TS}}$ . This suggests a possible use as a biofertilizer for agricultural use. At the same time, the organic acids present  $91.3 \pm 6.1 \text{ mg/g}_{\text{TS}}$  (i.e., levulinic, maleic and malonic acids) could be extracted and used for the production of biopolymers and fine-chemicals (ethyl levulinate,  $\gamma$ -valerolactone). Finally, esterifiable lipids have also been identified ( $74.3 \pm 2.1 \text{ mg/g}_{\text{TS}}$ ) that could be used for biodiesel production.

Table 1. Chemical composition of microalgae (*Chlorella Vulgaris*).

| Total solids (TS) composition                  |   |
|--|---|
| <b>Total Lipids</b>                            | <b><math>85.3 \pm 3.1 \text{ mg/g}_{\text{TS}}</math></b>   |
| <i>Esterifiable lipids (FAMES)</i>             | <i><math>74.3 \pm 2.1 \text{ mg/g}_{\text{TS}}</math></i>   |
| <b>Proteins</b>                                | <b><math>556 \pm 25 \text{ mg/g}_{\text{TS}}</math></b>     |
| <b>Easy Hydrolysable Sugars (EHS)</b>          | <b><math>91.3 \pm 6.1 \text{ mg/g}_{\text{TS}}</math></b>   |
| <i>Arabinose</i>                               | <i><math>3.9 \pm 0.2 \text{ mg/g}_{\text{TS}}</math></i>    |
| <i>Glucosamine</i>                             | <i><math>5.9 \pm 0.2 \text{ mg/g}_{\text{TS}}</math></i>    |
| <i>Galactose</i>                               | <i><math>9.4 \pm 0.2 \text{ mg/g}_{\text{TS}}</math></i>    |
| <i>Glucose</i>                                 | <i><math>59.5 \pm 0.2 \text{ mg/g}_{\text{TS}}</math></i>   |
| <i>Xylose</i>                                  | <i><math>0.5 \text{ mg/g}_{\text{TS}}</math></i>            |
| <b>Lignin</b>                                  | <b><math>49 \text{ mg/g}_{\text{TS}}</math></b>             |
| <b>Ashes</b>                                   | <b><math>56 \text{ mg/g}_{\text{TS}}</math></b>             |
| <b>Other compounds (i.e. carboxylic acids)</b> | <b><math>162.4 \pm 31.1 \text{ mg/g}_{\text{TS}}</math></b> |

#### Conclusions

Microalgae (*Chlorella Vulgaris*) deriving from wastewater treatment was characterized in order to determine its potential to be valorised as potential source of biofuels and biochemicals. The high content of proteins and organic acids suggests the main use for the production of biofertilizer and biopolymers, respectively, reducing the total costs of wastewater treatment with the obtaining of products with high added value.

#### Acknowledges

This work was supported in part by the Italian Ministry of Foreign Affairs and International Cooperation. Grant number CN23GR08.

#### References

1. di Bitonto L., Todisco S, Gallo V, Pastore C. (2020). *Bioresour. Technol. Rep.* 9 (2020), 100382.
2. di Bitonto L, Locaputo V, D'Ambrosio V, Pastore C. *Appl. Energy* 259 (2020), 114163.



# Microalgae as sustainable and potential feedstock for the production of biofuels and fine chemicals

<sup>1</sup>Luigi di Bitonto, <sup>2</sup>Anjie Li and <sup>1</sup>Carlo Pastore


<sup>1</sup>CNR-IRSA, via De Blasio 5, 70132, Bari, Italy, e-mail: luigi.dibitonto@ba.irsa.cnr.it

<sup>2</sup>No.19, Xijiekouwai Street, Haidian District, Beijing 100875, China

## Introduction


As a result of the growing world population and rapid industrialization, the increasing production of municipal wastewater has emerged as one of the major environmental problems. **Organic and inorganic pollutants** of various origins, including **micropollutants** and **heavy metals**, are discharged into water bodies nearby industrial and agricultural activities. The presence of excess nutrients such as **nitrogen (N) and phosphorus (P)** is the cause of eutrophication of **water bodies** and the **resulting environmental problems**. For this reason, there is a need to develop treatment processes that can remove these nutrients before wastewater is discharged.

## "The problem of wastewater management"



In this sense, the use of algae as a means of bioremediation of wastewater can effectively extract nitrogen and phosphorus from wastewater, keeping dissolved oxygen levels constant and helping to reduce the pathogens and fecal bacteria present in wastewater

## "The use of algae for bioremediation of wastewater"




In addition, it is also an **environmentally sustainable option** as it has the ability to convert carbon dioxide into chemicals and useful products, thus helping to reduce **greenhouse gas emissions**

However, **the cost of this technology** is the main factor that limits its application on an **industrial scale**

## Aim of work

In this work, a detailed analysis of the **chemical composition of microalgae (Chlorella Vulgaris)** grown using **wastewater** as a substrate was carried out. The identification and quantification of **Total Lipids, Proteins, Easy Hydrolysable Sugars (EHS), Lignin, Ashes** and **Carboxylic Acids** were performed in order to identify the possible prospects of its possible reuse for **the production of platform molecules and fine chemicals**

## "Algae biomass valorization"



## Results and discussion

### Chemical characterization of microalgae "Chlorella Vulgaris"

#### Total solids (TS) composition

|  |                                     |
|--|-------------------------------------|
| <b>Total Lipids</b>                            | <b>85.3 ± 3.1 mg/g<sub>TS</sub></b> |
| <b>Proteins</b>                                | <b>556 ± 25 mg/g<sub>TS</sub></b>   |
| <b>Easy Hydrolysable Sugars (EHS)</b>          | <b>91.3 ± 6.1 mg/g<sub>TS</sub></b> |
| Arabinose                                      | 3.9 ± 0.2 mg/g <sub>TS</sub>        |
| Glucosamine                                    | 5.9 ± 0.2 mg/g <sub>TS</sub>        |
| Galactose                                      | 9.4 ± 0.2 mg/g <sub>TS</sub>        |
| Glucose  | 59.5 ± 2.3 mg/g <sub>TS</sub>       |
| Xylose   | 0.5 mg/g <sub>TS</sub>              |
| <b>Lignin</b>                                  | <b>49 mg/g<sub>TS</sub></b>         |
| <b>Ashes</b>                                   | <b>56 mg/g<sub>TS</sub></b>         |
| <b>Other compounds (i.e. Carboxylic Acids)</b> | <b>162.4 ± 31 mg/g<sub>TS</sub></b> |

The **protein content** is the main component with a **value of 556 ± 25 mg/g<sub>TS</sub>**. This suggests a possible use as a **biofertilizer** for agricultural use. At the same time, the **Carboxylic Acids** present **162.4 ± 31 mg/g<sub>TS</sub>** (i.e., levulinic, maleic and malonic acids) could be extracted and used for the production of **Biopolymers and fine-chemicals**



**biofertilizers and biopolymers**

## Conclusions

Microalgae (*Chlorella Vulgaris*) deriving from **wastewater treatment** was characterized in order to determine its potential to be valorized as potential source of biofuels and biochemicals. The high content of **Proteins** and **Carboxylic Acids** suggests the main use for the production of **Biofertilizers** and **Biopolymers**, respectively, reducing the total **costs of wastewater treatment** with the obtaining of products with high added value.

## Acknowledges

This work was supported in part by the Italian Ministry of Foreign Affairs and International Cooperation. Grant number CN23GR08.